## Technical Datasheet

Dispurez 101

Issue 3 - 04/19



## Description

Dispurez 101 is a high Tg, hard, crystalline waterborne polyurethane dispersion suitable for clear protective top coats and lacquers. Upon application, the water evaporates to yield a tough, glossy transparent film that exhibits excellent water and chemical resistance. The product displays rapid hardness development once dry and is therefore suitable for a wide range of end applications in surface coatings industries, in particular as a hard protective coating for rigid plastic substrates.

## **Typical Properties**

Туре	Aliphatic polycarbonate
Appearance - 20°C	Translucent liquid
Dispersion Type	Anionic
Viscosity (cP @ 20°C)	175
Solids Content (%)	31 <u>+</u> 1
pH	9.5
Particle Size (nm)	55
Pencil Hardness	Н
Tensile Strength (MPa)	26
Elongation at Break (%)	120
Persoz Hardness (s)	300
MFFT (°C)	< -10
Tg (°C)	58

## **Typical Applications**

 $\cdot$  Tough coatings for rigid plastics including uPVC/ABS/HIPS

Incorez Limted, Miller Street, Preston, Lancashire, PR1 1EA, England t: +44(0)1772 201964 f: +44(0)1772 255194 e: info@incorez.com www.incorez.com